Freeform Search

| Database: | US Pre-Grant Publication Full-Text Database US Patents Full-Text Database US OCR Full-Text Database EPO Abstracts Database JPO Abstracts Database Derwent World Patents Index IBM Technical Disclosure Bulletins | · |
|-----------|--|---|
| Term: | L27 and "thermal insulation" | |
| Display: | Documents in <u>Display Format</u> : - Starting with Number 1 | |
| Generate: | ○ Hit List 	 Hit Count ○ Side by Side ○ Image | |
| | Search Clear Interrupt | |
| | Search History | |

DATE: Wednesday, October 06, 2004 Printable Copy Create Case

| Set Name side by side | Query | Hit Count | Set Name result set |
|--------------------------|---|-----------|---------------------|
| DB=PGI | PB, USPT, USOC, EPAB, JPAB, DWPI, TDBD; PLUR = YE | S; OP=ADJ | |
| <u>L28</u> | L27 and "thermal insulation" | 28 | <u>L28</u> |
| <u>L27</u> | (sealed enclosure) and (heat sink) | 462 | <u>L27</u> |
| <u>L26</u> | (hermetical enclosure) and (heat sink) | 1 | <u>L26</u> |
| <u>L25</u> | (vacuum enclosure) and (heat sink) | 124 | <u>L25</u> |
| <u>L24</u> | vacuum enclosure heat sink | 0 | <u>L24</u> |
| <u>L23</u> | heat sink evacuated enclosure | 0 | <u>L23</u> |
| <u>L22</u> | L20 and "heat sink" | 37 | <u>L22</u> |
| <u>L21</u> | L20 and "thermoelectric cooler" | 2 | <u>L21</u> |
| <u>L20</u> | evacuated enclosure | 1231 | <u>L20</u> |
| <u>L19</u> | L12 and "air free housing" | 0 | <u>L19</u> |
| <u>L18</u> | L12 and "vacuum" | 257 | <u>L18</u> |
| <u>L17</u> | L12 and "insulated casing" | 26 | <u>L17</u> |
| <u>L16</u> | L12 and "insulated chamber" | 2 | <u>L16</u> |
| <u>L15</u> | L12 and "insulated container" | 2 | <u>L15</u> |
| <u>L14</u> | L12 and "evacuated container" | 0 | <u>L14</u> |
| <u>L13</u> | L12 and "cooling component" | . 2 | <u>L13</u> |
| | | | |

| <u>L12</u> | (heat exchanger) and (downhole) | 585 | <u>L12</u> |
|-------------|---|--------|------------|
| <u>L11</u> | vacuum container heat exchanger | 2 | <u>L11</u> |
| <u>L10</u> | thermally insulated heat exchanger | 14 | <u>L10</u> |
| <u>L9</u> | thermally insulated cooler | 25 | <u>L9</u> |
| <u>L8</u> · | thermally hindering material | 0 | <u>L8</u> |
| <u>L7</u> | thermally hndering material | ` 0 | <u>L7</u> |
| <u>L6</u> | (evacuated container) and (thermoelectric cooler) | 0 | <u>L6</u> |
| DB=US | SPT; PLUR=YES; OP=ADJ | | |
| <u>L5</u> | (eutectic material) and (phase change) | 26 | <u>L5</u> |
| <u>L4</u> | L1 and "valve" | 0 | <u>L4</u> |
| <u>L3</u> | L and "valve" | 161041 | <u>L3</u> |
| <u>L2</u> | L1 and "Q1" | 0 | <u>L2</u> |
| <u>L1</u> | 6519955.pn. | 1 | <u>L1</u> |

END OF SEARCH HISTORY

Freeform Search

| Database: | US Pre-Grant Publication Full-Text Database US Patents Full-Text Database US OCR Full-Text Database EPO Abstracts Database JPO Abstracts Database Derwent World Patents Index IBM Technical Disclosure Bulletins |
|---|--|
| Term: | (eutectic material) and (phase change) |
| Display: | Documents in Display Format: Starting with Number 1 |
| Generate | : O Hit List @ Hit Count O Side by Side O Image |
| | Search Clear Interrupt |
| | Search History |
| DATE: Wednes | sday, October 06, 2004 Printable Copy Create Case |
| Set Name Query side by side DB=USPT; Pl | Hit Count Set Name result set LUR=YES; OP=ADJ |
| , | tic material) and (phase change) 26 <u>L5</u> |

0

0

1

161041

<u>L4</u>

<u>L3</u>

<u>L2</u>

<u>L1</u>

END OF SEARCH HISTORY

L1 and "valve"

L and "valve"

L1 and "Q1"

6519955.pn.

<u>L4</u>

<u>L3</u>

<u>L2</u>

<u>L1</u>